

INSTALLATION INSTRUCTION

LED RECHARGEABLE LIGHT WITH STAND



SPECIFICATIONS

Model	VT-4822
Watts	20
Lumens	1600
BeamAngle	100
PF	>0.95
CRI	>70
LED Chip Type	SMD
IP Rating	IP44
Unit Color	Green
Body Type	Plastic + Aluminium
Operation Temperature	-25°C to +50°C
Input Power	AC:100-240V,50/60Hz
Dimension	208x204x355mm

INTRODUCTION & WARRANTY

2 YEAR
WARRANTY*

Thank you for selecting and buying V-TAC product. V-TAC will serve you the best. Please read these instructions carefully before starting the installing and keep this manual handy for future reference. If you have any another query, please contact our dealer or local vendor from whom you have purchased the product. They are trained and ready to serve you at the best.

The warranty is valid for 2 years from the date of purchase. The warranty does not apply to damage caused by incorrect installation or abnormal wear and tear. The company gives no warranty against damage to any surface due to incorrect removal and installation of the product. This product is warranted for manufacturing defects only.

SAFETY INSTRUCTIONS FOR BATTERIES

1. Never attempt to open for any reason.
2. Do not store in locations where the temperature may exceed 40 °C.
3. Charge only at ambient temperatures between 4 °C and 40 °C.
4. Charge only using the charger provided with the tool.
5. When disposing of batteries, follow the instructions given in the section "Protecting the environment".
6. Do not cause short circuits. If connection is made between the positive (+) and negative (-) terminal directly or via accidental contact with metallic objects, the battery is short circuited and an intense current will flow causing heat generation which may lead to casing rupture or fire.
7. Do not heat. If batteries are heated to above 100 °C, sealing and insulating separators and other polymer components may be damaged resulting in electrolyte leakage and/or internal short circuiting leading to heat generation causing rupture or fire. Moreover do not dispose of the batteries in fire, explosion and/or intense burning may result.
8. Under extreme conditions, battery leakage may occur. When you notice liquid on the battery, proceed as follows:
 - Carefully wipe the liquid off using a cloth. Avoid skin contact.
 - In case of skin or eye contact, follow the instructions below:
 - i. Immediately rinse with water. Neutralize with a mild acid such as lemon juice or vinegar.
 - ii. In case of eye contact, rinse abundantly with clean water for at least 10 minutes. Consult a physician.

Fire hazard! Avoid short-circuiting the contacts of a detached battery. Do not incinerate the battery.

SAFETY INSTRUCTIONS FOR CHARGER

1. Use the charger provided with the tool only to charge the battery
2. Never attempt to charge non-rechargeable batteries.
3. Have defective cords replaced immediately.
4. Do not expose to water.
5. Do not open the charger.
6. Do not probe the charger.
7. The charger is intended for indoor use only.

SAFETY WARNING

This is not a toy; children should not permit to use it. This is a DIY product, all electronic parts fixed already, any intention of opening the light or changing the design of the floodlight is prohibitive.

Do not attempt to replace or change or the diode lights! If the protective glass is cracked or broken, it must be replaced before the Rechargeable Floodlight can be used again.

PACKAGING CONTENTS

1. RECHARGEABLE FLOODLIGHT (1PC)
2. AC CHARGER (1PC)
3. DC CAR CHARGER (1PC)
4. USB CHARGER (1PC)

OPERATION

1. Ensure electricity is switched OFF.
2. Connect the AC Charger to the socket and the other wire to the product
3. Switch on the power if above steps done properly without any mistakes.
4. When the light is charging the green light will appear.